

ProLine® Residential Gas

Atmospheric Vent Water Heater



There's nothing standard about commercial grade.

- Blue Diamond® glass coating is a patented commercial-grade formula that provides superior tank protection and corrosion resistance compared to the industry standard glass lining.
- Enhanced flow brass drain valve is a tamper-resistant, ball-type drain valve that's designed for easy operation.
- Heat trap nipples help mitigate standby heat loss by reducing the amount of heat lost through the connected pipes.
- Coregard™ anode rods feature a stainless-steel core that allows the anode to be secured in place, extending the life of the water heater.

What does it mean to be commercial grade?

- As a leader in commercial water heating, A. O. Smith understands the importance of commercial hot water delivery and require the same standard and performance in our residential products.
- Many of the same components that are in commercial water heaters are in residential water heaters and are made in-house at APCOM parts division.
- All products are run through a rigorous quality and endurance testing and inspection, providing a tougher residential product.

A water heater is an investment in your home's value and your family's comfort. Make the easy choice, an A. O. Smith ProLine® Commercial-Grade residential water heater, and get the most for your money.

OTHER FEATURES

SELF-POWERED ELECTRONIC GAS CONTROL VALVE

- Standard gas water heaters are equipped with a self-powered electronic gas valve with intelligent control logic.
- Internal microprocessor that provides enhanced operating parameters and tighter differentials for precise sensing and faster heating response to optimize performance.
- Uses a thermopile to generate the power needed to operate the electronic gas control without requiring an external power source.
- Incorporates an LED status indicator that monitors system operation and service diagnostics.

GREEN CHOICE® GAS BURNER

- Patented eco-friendly burner design reduces NOx emissions by up to 33% and complies with Low-NOx emission requirements of less than 40 ng/J.

DYNACLEAN™ DIFFUSER DIP TUBE

- Reduces lime and sediment buildup and maximizes hot water output.
- Made from long-lasting PEX cross-linked polymer.

PUSH-BUTTON PIEZO IGNITOR

- Makes lighting the pilot fast and easy with one-hand push-button spark ignition.

HIGH UNIFORM ENERGY FACTOR (UEF)

- Eco-Friendly non-CFC foam insulation, external heat traps and specially designed combustion chamber combine to produce a high UEF for maximum savings on operating costs.

CSA CERTIFIED AND ASME RATED T&P RELIEF VALVE

6-YEAR (ProLine®) OR 8-YEAR (ProLine® Master) LIMITED TANK AND PARTS WARRANTY

For complete information, consult written warranty or go to hotwater.com

Scan the QR code to visit hotwater.com >

