

ProLine® XE Adapt™ Series Premium Condensing Gas Tankless



Ultra flexible for easy installation. Premium features for easy selling.

- 160k, 180k, 199k BTU/h
- 9k BTU min. input
- 22:1 Turndown Ratio (199k configurations)
- Max Flow Rate 10.5 GPM; 0.4 GPM activation; 0.26 GPM for continuous fire
- 0.95 UEF, ENERGY STAR® certified
- Ultra Low NOx – Complies with SCAQMD Rule 1146.2*

*Ultra Low NOx – Complies with SCAQMD Rule 1146.2 and other air quality management districts with similar NG NOx emission requirements of 14 ng/J or 20 ppm. Complies with SJVAPCD Rule 4308 and other air quality management districts with similar LP NOx emission requirements of 77 ppm.

- Exhaust venting, 2" PVC up to 75' (23m); 3" PVC up to 150' (45.7m)
- Cat. IV venting may be used
- Flexible venting with PVC, CPVC, Polypropylene, or ABS Pipe (solid core only)
- Integrated recirculation pump
- Optional remote activation (Title 24) kits available

Adapt Series Premium Condensing Gas Tankless Water Heaters deliver robust, on-demand performance and the flexibility to install in practically any residential setting.

OTHER FEATURES

X3® SCALE PREVENTION TECHNOLOGY

Integrated into all X3® models; optional accessory for Bypass Manifold (M) models

- No annual descaling required
- No scale buildup means the heater maintains like-new performance longer
- Extends life of unit up to three times versus unprotected unit

HEAVY DUTY STAINLESS-STEEL HEAT EXCHANGER DESIGN

- Single stainless steel, heavy-duty heat exchanger design eliminates most internal welds and improves overall efficiency
- More resilient to scale buildup and corrosion

ULTIMATE FLEXIBILITY - EASE OF INSTALLATION

- Universal indoor or outdoor installation; Outdoor Vent Cap Kit sold separately
- Field convertible from Natural Gas to Liquid Propane, kit included
- ½" Gas Line or larger
- Exhaust venting, 2" PVC up to 75' (23m); 3" PVC up to 150' (45.7m)
- Cat. IV venting may be used
- Flexible venting with PVC, CPVC, Polypropylene, or ABS Pipe (solid core only)

- Pressure Relief Valve included with X3 models
- Outdoor rated power cord standard on every unit
- Cascade up to 12 units with single cable per heater, cable included
- Approved for installation in manufactured homes

SAFETY FEATURES

- Qualifies as Lead Free under the Safe Drinking Water Act
- Exhaust and water temperature safety control
- Internal freeze protection system to -5°F (-21°C)

WARRANTY

- No hardwater exclusions on X3 models; exclusions apply to M models
- 15-year limited warranty on heat exchanger in residential applications
- 5-year limited warranty on all parts in residential applications
- 1-year limited warranty on heat exchanger and parts in commercial applications

For more information about this product, visit [hotwater.com](https://www.hotwater.com).

Scan the QR code to the website >

